



- Concept:**
- Housing from insulated Sandwich elements.
 - 2 compartments:
 - √ Compartment 1 is tight and acts as a bund
 - √ Compartment 2 is the technical room
 - Integrated Anti freeze heating
 - Outside colour: white

Type	Volume	Length	width	height	Kg
BL-4000	4000	2860mm	1170mm	2320mm	700
BL-5000	5000	3370mm	1530mm	2317mm	750
BL-7500	7500	4600mm	1530mm	2317mm	980
BL-10000	10000	5820mm	1530mm	2317mm	1250

Filling point: Separated Stainless Steel filling compartment integrated into Blue 1 panel. Separate removable door to access:

- 2" dry coupling
- Overfill protection plug type Fafnir
- Level indicator
- Overfill prevention
- Optionals:
 - √ Active overfill protection alarm with reset button

Refuelling: *Installed into compartment 2*

- Standard foreseen with hose balancer system with 5m operational length.
- Elaflex automatic Ad Blue nozzle with integrated magnet.
- Max flow 40l/min.
- Complete Stainless steel Blue 1 panel with isolated door.
- Available in single side version or double side version.
- Not approved for public use
- Optionals:
 - √ Hose reel for operational length up to 8 meters
 - √ Active minimum level alarm with LED indication.
 - √ Timer function (maximum dispensing time)
 - √ Function key deactivation dispenser
 - √ Extension for satellite connexion.

Flow measurement:

1. *Display type ALX 701:*

- Performances:
- Command for 1 pump & display of delivered fuel.
 - Storage of litre totals.
 - Calibration factor of the measuring room.
 - Output 10 pulses pro litre

Wireless communication: Endress & Hauser Fieldgate GSM (optional)

Electrical connections:

- For non hazardous area
- 1 x 230VAC, 16A (3 x 2.5mm²)
- EU Directive Low Voltage 73/23/EEG, updated 93/68/EEG