



- Concept:**
- Housing from insulated Sandwich elements.
 - 2 compartments:
 - √ Compartment 1 is tight and acts as a bund
 - √ Compartment 2 is the technical room with access door.
 - Integrated Anti freeze heating
 - Outside colour: white,

Type	Volume	Length	width	height	Kg
BL-4000	4000	2860mm	1170mm	2320mm	700
BL-5000	5000	3370mm	1530mm	2317mm	750
BL-7500	7500	4600mm	1530mm	2317mm	980
BL-10000	10000	5820mm	1530mm	2317mm	1250

- Tank:** *Installed into compartment 1*
- Type: Single wall
 - Material: Polyethylene
 - Sensor: Level sensor 4-20mA
 - Pump: Submersible pump type LEADER Ecodiver 1000A

- Filling point:** Filling point in technical room.
- Complete stainless steel piping circuit
 - 2" dry coupling
 - Overfill protection plug type Fafnir
 - Level indicator integrated into electrical board or separated box
- Optionals: √ Active overfill protection alarm with reset button

Refuelling: Standard foreseen for connexion to 1 satellite

- Optionals: √ Multiple satellite version (up to 4)
 √ Timer function

Wireless communication: Endress & Hauser Fieldgate GSM (optional)

Electrical connections:

- For non hazardous area
- 1 x 230VAC, 16A (3 x 2.5mm²)
- EU Directive Low Voltage 73/23/EEG, updated 93/68/EEG