



Standard:



double skin tank
(2 tanks)



movable roof
for maintenance



nozzle with automatic
shut off & automatic
nozzle holder



stainless steel
construction
& piping



long hose



sound & light
overfill alarm



flow meter with LCD



calibrated meter
with value display

 **for trucks & passenger cars** 
available for Petrol Stations

capacities: 3.000 • 4.000 • 6.000 ltr

Options:



on / off pump
key switch



IQ terminal
& telemetry



heated hose



your branding



2" dry break coupling
for cistern filling



submersible pump
with dry run
protection



mechanical level
indicator



openings for forklift

CAPACITIES, DIMENSIONS & WEIGHT

FRONT DISPENSER



SIDE DISPENSERS



TECHNICAL SPECIFICATION

Power Supply	1 x 230V / 50 Hz
Pump Efficiency	max. 40 ltr / min
Pump Pressure	2,5 bar
Dry Break Coupling	DIN d-50 mm
Heating	119 - 170 W
Overfill Protection	230 V / 50 Hz
Cable Connection	3 x 1,5 - 2,5 mm ²
Operating Conditions	- 20°C - + 45°C
Hose Length	up to 4 mtr

All SMART **comfort** Units (FRONT & SIDE DISPENSERS) can be available in following nozzle versions:

MATERIALS

External tank	fiberglass
Inner tank	polyethylene
Pipes	stainless steel
Hose	EPDM DIN 16
Nozzle	stainless steel & PE cover



Vandotec NV
Nijverheidsstraat 49
B-8970 Popering

Tel. +3257335251
Fax. +3257333161
E-mail: info@vandotec.be
website: www.vandotec.be