



 for trucks & passenger cars 

capacity: 1.500 ltr

**Options:**



on/off pump  
key switch



your branding



IQ terminal  
& telemetry



sound & light  
leakage & overfill  
alarm



flow meter  
with LCD



nozzle with automatic  
shut off & automatic  
nozzle holder



submersible pump  
with dry run  
protection



hose reel

**Standard:**



double skin tank  
(2 tanks)



movable roof  
for maintenance



nozzle with  
automatic  
shut off



stainless steel  
construction  
& piping



loose hose



mechanical  
level indicator



openings for forklift



2" dry break  
coupling for cistern  
filling



flow meter  
with LCD



pump with  
flow rate up to  
32 ltr/min

# TULIP 1500 - DIMENSIONS, CAPACITY & WEIGHT



## TULIP basic



## TULIP premium



TULIP storage can be easily connected to free standing dispenser.

## TECHNICAL SPECIFICATION

<b>Power Supply</b>	1 x 230V / 50 Hz
<b>Tulip basic Pump Efficiency</b>	max. 32 ltr / min
<b>Tulip premium Pump Efficiency</b>	max. 40 ltr / min
<b>Dry Break Coupling</b>	DN d-50 mm
<b>Cable Connection</b>	3 x 1,5 - 2,5 mm <sup>2</sup>
<b>Operating Conditions</b>	- 20°C - + 45°C
<b>Hose Length</b>	up to 6m
<b>Flowmeter Accuracy</b>	+ /- 1 %

## MATERIALS

<b>External tank</b>	fiberglass
<b>Inner tank</b>	polyethylene
<b>Pipes</b>	stainless steel
<b>Hose</b>	EPDM DN 16
<b>Nozzle</b>	stainless steel & PE cover



**Vandotec NV**  
Nijverheidsstraat 49  
B-8970 Poperinge

Tel. +3257335251  
Fax. +3257333161  
E-mail: [info@vandotec.be](mailto:info@vandotec.be)  
website: [www.vandotec.be](http://www.vandotec.be)